



### Steps to clean your Katadyn cartridge:

1. Trace the inlet water hose back from the cartridge housing until you reach the on/off valve. Turn this to 'off'.
2. Turn on the Triflow filtered water lever on the tap to drain excess water from the system. Leave the tap on.
3. Remove your stainless steel cartridge housing by lifting it from the parking bracket. Place the unit in a bucket or on a towel.
4. Remove the Katadyn cartridge from the housing by twisting the housing lid and lifting out the cartridge with the lid. The bucket or towel will catch any excess water.
5. Wash out the stainless steel housing with warm soapy water and rinse thoroughly.
6. Unscrew the cartridge from the housing lid and place the cartridge carefully in your sink.
7. Under running tap water (untreated water is fine for this), lightly scrub the ceramic outer surface of the cartridge with a plastic dish brush or soft cleaning pad.

DO NOT use any cleaning products, chemicals or soaps as these may become imbedded in the ceramic and will affect your drinking water.

DO NOT use steel wool or other harsh scourers as these may damage the ceramic.

8. Before you screw the cleaned cartridge back into the housing lid, wet the two rubber o-rings on the screw end, then screw this back into the lid. Be careful to ensure a snug fit but do not over tighten or the seal may be broken.
9. Slide the cartridge into the stainless steel housing and twist to close the lid, ensuring a proper seal. Replace the housing on the parking bracket.
10. Turn the inlet on/off valve back to 'on'. Water will flow from the tap spout. Allow the flow of water to flush the system for 30 seconds while watching the under-bench system for leaks. This will also flush out any air from the system.

You should notice a significant improvement in water flow. You have successfully cleaned your Katadyn filter cartridge.