



### **Steps to replace your Katadyn cartridge:**

1. Order a new Katadyn filter cartridge from In Residence, your certified Triflow stockist.
2. Trace the inlet water hose back from the cartridge housing until you reach the on/off valve. Turn this to 'off'.
3. Turn on the Triflow filtered water lever on the tap to drain excess water from the system. Leave the tap on.
4. Remove your stainless steel cartridge housing by lifting it from the parking bracket and place it in a bucket or on a towel.
5. Remove the Katadyn cartridge from the housing by twisting the housing and lifting out the cartridge with the lid. The bucket or towel will catch any excess water.
6. Unscrew the cartridge from the lid of the housing and dispose of this with your normal rubbish.
7. Wash out the stainless steel housing with warm soapy water and rinse thoroughly.
8. Before you screw the new cartridge into the lid of the housing, wet the two rubber o-rings on the screw end, then screw into the lid. Be careful to ensure a snug fit but do not over tighten or the seal may be broken.
9. Slide the cartridge into the stainless steel housing and twist to close the lid, ensuring a proper seal. Replace the housing on the parking bracket.
10. Turn the inlet on/off valve back to 'on'. Water will flow from the tap spout. Allow the flow to flush the system for 30 seconds while watching the under-bench system for any leaks. This will also flush out any air from the system.

You have now successfully installed your new Katadyn filter cartridge.